

ENIGMA

Product Specification	Carpet Tiles
Pile Yarn	100% SD Nylon (Antron Lumena)
Construction	Pattern Structured Cut/Loop
Dyeing Method	Solution
Primary Backing	Non Woven Polyester/Nylon
Secondary Backing	Bitumen with Glass Fibre
Pile Weight	780g/m ² ±
Total Weight	4620g/m ² ±
Pile Height	3mm nominal
Total Thickness	6.7mm nominal
Gauge	1/12 th
Pile Density	0.177g/cm ³ ±
Number of Tufts	226,560m ² ±
Tile Size	50cm x 50cm

Technical Specification – Overall Performance Rating	
Classification	Heavy Contract
Flammability BS 4790: 1987 (1996)	Hot Metal Nut Low Radius
Flammability Euro Class	CFL - S1
Static Protection	Passes IBM/ICL
Castor Chair EN 985/A	Pass > 2.4
Colour Fastness	All Tests 4-5 or Better
Noise Impact Test BS EN ISO 140-8	21dB

Installation
 All carpet tiles should be fitted in accordance with BS5325: 1996. Adequate protection should be allowed under roller castor chairs.

Recommended adhesives
 For Permanent Bonding:.....Styccobond F3
 For Release Bonding:.....Styccobond F41

Maintenance
 Enigma should be vacuumed regularly, commercial cleaning using the 'Envirodry System' or the 'Hot Water Extraction' method is recommended depending on conditions. Spot clean immediately on spill. For further advice on maintenance contact: **Simon Dickinson** on **0115 989 9210**



15 Year Limited Wear Warranty, contact the office for details.



Birch Carpets
 Hazel Park Mills
 318 Coleford Road
 Sheffield
 S9 5PH
 Tel 0114 243 1230
 Fax 0114 243 5118
 Email info@birchcarpets.co.uk
 Website www.birchcarpets.co.uk

