

# HI TECH

Product Specification	CARPET TILES
Pile Yarn	100% SD Nylon
Construction	Loop Pile
Dyeing Method	Solution
Primary Backing	Colbac
Secondary Backing	Bitumen
Pile Weight	550g/m <sup>2</sup>
Total Weight	4400/m <sup>2</sup>
Pile Height	3mm nominal
Total Thickness	6.5mm nominal
Gauge	1/10 <sup>th</sup>
Tile size	50cm x 50cm

## Technical Specification – Overall Performance Rating

Classification	Heavy Contract
Flammability BS 4790: 1987 (1996)	Hot Metal Nut Low Radius
Flammability Euro Class	CFL – S1=P1 Pass
Static Protection ISO 6356	IBM/ICL at above 40% RH
Castor Chair DIN 54324	Exceeds Min Requirements
Colour Fastness	All tests 5 or better
Green Guide Rating	This product has been awarded the highest green guide A+
Noise Impact Test BS EN ISO 140-8	21.0 dB
Part 8: 1998	Special order, Comfort backing will reduce it to over 27 dB

## Installation

All carpets should be fitted in accordance with BS5325: 1996.

### Recommended adhesives:

For Permanent Bonding:.....Styccobond F3

For Release Bonding:.....Styccobond F41

### Maintenance

Hi Tech® should be vacuumed regularly, commercial cleaning using the 'Envirodry System' or the 'Hot Water Extraction' method is recommended depending on conditions. Spot clean immediately on spill. For further advice on maintenance contact **Simon Dickinson** on **0115 989 9210**.

**10 Year Limited Wear Warranty Contact the office for details.**



**Birch Carpets**  
 Hazel Park Mills  
 318 Coleford Road  
 Sheffield  
 S9 5PH  
**Tel** 0114 243 1230  
**Fax** 0114 243 5118  
**Email** info@birchcarpets.co.uk  
**Website** www.birchcarpets.co.uk

