

NEW DELTA TECH

PRODUCT SPECIFICATION

Pile Yarn.....	100% Polyamide 6
Construction.....	Tufted Cut Pile
Dyeing Method.....	Solution
Primary Backing.....	Non Woven Polyester
Secondary Backing.....	Bitumen with Glassfibre
Pile Weight.....	800g/m ² ±5%
Total Weight.....	4600g/m ² ±10%
Pile Height.....	3.0mm ±0.5mm
Gauge.....	1/10 th
Total Thickness.....	6.0mm ±0.5mm
Pile Density.....	0.120g/m ³ ±10%
Number of Tufts.....	195,000m ² ±5%
Tile Size.....	50cm x 50cm ±
Tiles per Box.....	20 (5m ²)
Colour Range.....	8

TECHNICAL SPECIFICATION

Permanent Antistatic.....	Yes
Walk on Test EN1815.....	< 2kV
Pass by IBM/ICL.....	Yes
Radiant Panel Test ISO13501.....	Cfl-S1
Hot Metal Nut BS4790.....	Low Radius of Effects of Ignition
Wear Resistance EN1307.....	Class 33
Light Fastness ISO 105 B02.....	6
Water Fastness ISO 105 E01.....	4-5
Rub Fastness ISO 105 X12.....	4-5

INSTALLATION

All carpets should be fitted in accordance with **BS 5325: 1996**.
Adequate protection should be allowed under roller castor chairs.

Recommended adhesives:

For Permanent BondingStyccobond F3
For Release BondingStyccobond F41

Maintenance:

New Delta Tech should be vacuumed regularly, commercial cleaning using the 'Host Dry Cleaning System' or the Hot Water Extraction method is recommended depending on conditions.



Birch International Carpets

Hazel Park Mills, 318 Coleford Road, Sheffield S9 5PH

Tel: 0114 243 1230

info@birchinternational.co.uk

www.birchinternational.co.uk

