

# ENYO

## Product Specification

## Carpet Tiles

Pile Yarn	100% Polyamide 6,6 (Antron Lumena)
Construction	Pattern Structured Loop
Dyeing Method	Solution
Primary Backing	Non Woven Polyester/Nylon
Secondary Backing	Bitumen with Glass Fibre
Pile Weight	650g/m <sup>2</sup> ±
Total Weight	4140g/m <sup>2</sup> ±
Pile Height	2.5mm nominal
Total Thickness	6.0mm nominal
Gauge	1/12 <sup>th</sup>
Pile Density	0.186g/cm <sup>3</sup> ±
Number of Tufts	227,000m <sup>2</sup> ±
Tile Size	50cm x 50cm

## Technical Specification – Overall Performance Rating

Classification	Heavy Contract
Flammability BS 4790: 1987 (1996)	Hot Metal Nut Low Radius
Flammability Euro Class	CFL - S1
Static Protection	Passes IBM/ICL
Castor Chair EN 985/A	Pass > 2.4
Colour Fastness	All Tests 4-5 or Better
Noise Impact Test BS EN ISO 140-8	21dB
Bre global green guide rating	This product has been awarded the highest green guide rating A+

## Installation

All carpet tiles should be fitted in accordance with BS5325: 1996. Adequate protection should be allowed under roller castor chairs.

### Recommended adhesives

For Permanent Bonding:.....Styccobond F3  
For Release Bonding:.....Styccobond F41

### Maintenance

Enyo should be vacuumed regularly, commercial cleaning using the 'Envirodry System' or the 'Hot Water Extraction' method is recommended depending on conditions.

Spot clean immediately on spill.

For further advice on maintenance contact:

**Simon Dickinson** on **0115 989 9210**



*10 Year Limited Wear Warranty, contact the office for details.*



**Birch Carpets**  
Hazel Park Mills  
318 Coleford Road  
Sheffield  
S9 5PH  
Tel 0114 243 1230  
Fax 0114 243 5118  
Email [info@birchcarpets.co.uk](mailto:info@birchcarpets.co.uk)  
Website [www.birchcarpets.co.uk](http://www.birchcarpets.co.uk)



Cert. ENP479

