NOVA TECH

Product Specification	NOVA TECH Broadloom
Pile Yarn	100% Nylon
Construction	Tufted Loop Pile
Dyeing Method	Solution Dyed
Backing	Impervious Gel & Action Back
Pile Weight	550g/m² ±
Total Weight	1620g/m² ±
Pile Height	3.5mm
Gauge	1/10 th
Tuft Density	164,000/m²
Width	4m
Standard Roll	30m x 4m ±

Technical Specification – Overall Pe	erformance Rating
BSEN 1307 Classification	33 - Heavy Commercial
Flammability EN13501-1	Bfl S1
Electrostatic Properties	Walking Test <2.0KV Resistance ≥10 ¹⁰
Suitability	BS7131 (1) Heavy Contract
Impact Sound Reduction	24dB ISO 140-8
Colour Fastness to Light	7 ISO 105-B02
Colour Fastness to Rubbing	4 ISO 105-X12
Anti-Microbial Treatment	Ultra-Fresh*
Anti-Bacterial Treatment	Ultra-Fresh*
Anti-Fungal Treatment	Ultra-Fresh*
Anti-Dust Mite Treatment	Ultra-Fresh*
Suitable for Alzheimer's Patient Car	re Areas Yes

^{*} Nova Tech features Ultra-Fresh, an antimicrobial treatment, designed to combat the growth of bacteria (such as MRSA and E.Coli) and fungi (such as mildew and mould). For more information, please contact our office.

Installation

All carpets should be fitted in accordance with BS5325: 1996. Adequate protection should be allowed under roller castor chairs.

Recommended adhesives:

For Permanent Bonding: Styccobond F3
For Vertical Bonding: Styccobond F60

SEAMS MUST BE SEALED WITH SEAM SEALING ADHESIVE.

Maintenance

Nova Tech® should be vacuumed regularly, commercial cleaning using the 'Envirodry System' or the 'Hot Water Extraction' method is recommended depending on conditions. Spot clean immediately on spill.

For further advice on maintenance, contact Simon Dickinson on 0115 989 9210.

10 Year Limited Wear Warranty - Contact the office for details.



Birch Carpets

Hazel Park Mills 318 Coleford Road Sheffield S9 5PH

Tel 0114 243 1230 Fax 0114 243 5118

Email info@birchcarpets.co.uk Website www.birchcarpets.co.uk









