

SILK ROYAL

Product Specification	Heavy Contract Carpet
Pile Yarn	100% Polyester, 2-Ply
Construction	Cut Pile
Dyeing Method	Solution
Secondary Backing	Duo
Pile Weight	2650g/m ² ±
Total Weight	3550g/m ² ±
Pile Height	15mm nominal ±
Total Thickness	17mm nominal ±
Standard Roll Dimensions	25m x 4m Approx

Technical Specification - Overall Performance Rating

Classification	Heavy Domestic
Reaction to Fire	Efl
Luxury Class	LC5
Light Fastness	5-6
Thermal Resistance	0.175 m ² kW (1.75 TOG)

Installation

Suitability

A luxurious and hard wearing carpet made from resilient super soft stain resistant fibre, making it the ideal choice for the heart of your home.

Installation

Before installation, check for quality, texture, finish, colour match and that all carpet to be used in the same area is from the same dye batch. No claims will be considered after cutting and/or installation.

All carpets should be fitted in accordance with BS3525: 2001.

Recommended adhesives for Broadloom Carpet

For Permanent Bonding - Stycobond F3

SEAMS MUST BE SEALED WITH A SEAM SEALING ADHESIVE.

Maintenance

Silk Royal should be vacuumed regularly and spillages attended to immediately. Regularly daily suction vacuum cleaning and occasional hot water extraction is recommended. Most stains can be removed by a good quality purpose made cleaner following the manufacturer's instructions.

5 Year Limited Wear Warranty. Contact the office for details.



Birch Living


318 Coleford Road, Sheffield, S9 5PH

Tel 0114 243 1230

Fax 0114 243 5118

Email info@birchcarpets.co.uk

Website www.birchcarpets.co.uk



Birch Living ± specification represents a nominal 10%

Birch Living reserves the right to change or modify specifications without giving prior notice