

BARRIER TECH STRIPE

PRODUCT SPECIFICATION

	BROADLOOM	CARPET TILES
Pile Yarn	100% BCF Solution Dyed PA 6 Nylon	
Construction	Cut Pile Graphics	
Primary Backing	Colbac	
Secondary Backing	Vinyl	Bitumen Compound
Pile Weight	+/- 825 gms/m ²	+/- 825 gms/m ²
Total Weight	+/- 3525 gms/m ²	+/- 4570 gms/m ²
Pile Height	+/- 5mm	+/- 5mm
Total Thickness	7mm nominal	7.7mm nominal
Gauge	1/8th	1/8th
Standard Roll/Tiles	20m x 2m (approx)	500mm x 500mm

All sizes on broadloom include borders.

TECHNICAL SPECIFICATION

Performance Rating	Contract Class 32
Flammability BS4790: 1987 (1996)	Hot Metal Nut Test Pass
Castor Chair Rating	Pass
Tuft Anchorage	Greater than 3.5kg
Colour Fastness to Light	Class 7 scale 1-8

INSTALLATION

All carpets should be fitted in accordance with **BS 5325: 1996**.

Recommended adhesives for Broadloom:

For Permanent Bonding Styccobond F45
 For Wet Areas Broadloom Styccobond F74/F81

SEAMS MUST BE SEALED WITH A SEAM SEALING ADHESIVE

Recommended adhesives for Carpet Tiles:

For Permanent Bonding Styccobond F3
 For Release Bonding Styccobond F41

MAINTENANCE

Barrier Tech Stripe® should be vacuumed regularly, commercial cleaning using the "Envirodry System" or the **Hot Water Extraction** method is recommended depending on conditions. Spot clean immediately on spill. For further advice on maintenance contact Simon Dickinson on 0115 989 9210.

5 Year Limited Wear Warranty Contact the office for details.



Birch Carpets
 Hazel Park Mills, 318 Coleford Road, Sheffield, S9 5PH
Tel 0114 243 1230
Fax 0114 243 5118
Email info@birchcarpets.co.uk
www.birchcarpets.co.uk



Birch Carpets
 MANUFACTURING INSPIRATION

All specifications +/- are within 10% of specification.
 Birch Carpets reserve the right to change or modify specifications without giving prior notice.